



Cathedral Flooring

21mm Engineered

6mm veneer on 15mm WBP Pure Birch ply

Width	Species	Grade	Finish	Pack Size
140mm	European Oak	Character	Unfinished	1.344m ²
160mm	European Oak	Character	Unfinished	1.536m ²
180mm	European Oak	Character	Unfinished	1.728m ²
200mm	European Oak	Character	Unfinished	1.920m ²
240mm	European Oak	Character	Unfinished	1.728m ²
350mm	European Oak	Character	Unfinished	2.40m ²
<hr/>				
140mm	European Oak	Natural	Unfinished	1.344m ²
160mm	European Oak	Natural	Unfinished	1.536m ²
180mm	European Oak	Natural	Unfinished	1.728m ²
200mm	European Oak	Natural	Unfinished	1.920m ²
<hr/>				
160mm	European Oak	Character	UV Oil	1.536m ²
180mm	European Oak	Character	UV Oil	1.728m ²
200mm	European Oak	Character	UV Oil	1.920m ²
180mm	European Oak	Character	Smoked Hardwax Oil	1.728m ²
180mm	European Oak	Character	Rustic Hardwax Oil	1.728m ²
180mm	European Oak	Character	White Hardwax Oil	1.728m ²


Character grade has colour variation with sound filled knots. No sapwood allowed. Natural grade has colour variation with minimal knots. No sapwood allowed.

INFORMATION


- FSC® Certified by Rainforest Alliance.
- 6mm Veneer bonded to ply by cold press method.
- Pure Birch plywood substrate “WBP” (Water and Boil Proof).
- 1mm Bevel on the long edge, no bevel on short edge.
- Board length 2.4m with 3 full and 1 split board per pack. This avoids a regular joint structure when the floor has been laid.
- Must be fully bonded to a suitable substrate when used in conjunction with Underfloor Heating.
- Load bearing and can also be floated.




- Resistance 0.1235 m²k/w
Conductivity 0.17 W/m.k
Conductance 0035m²k/W
Togg 1.235 togg




Unfinished



UV Oil



Smoked Oak



Rustic Oil



White Oil



Winchester Hardwood Flooring Limited

The Foundry, London Road, Kings Worthy, Winchester, Hampshire SO23 7QA
Telephone +44 (0)1962 888577 Facsimile +44 (0)1962 888578
e-mail enquiries@whfloors.co.uk www.whfloors.co.uk